

skheme®

terra

terra



light





dark



iridium



maroon



PRODUCT SPECIFICATIONS	format	size	finish	thickness	slip rating	colour
	brick	60x240mm	matt	8-10mm	P4	all colours
	tile	150x150mm	matt	12-14mm	P4	dark iridium maroon
	tile	300x300mm	matt	11-13mm	P4	all colours
MATERIAL	terracotta					
VARIATION	V1					
TILE EDGE	non-rectified					

Colours shown in images may differ due to variations in photographic conditions and screen displays. Samples provided may not accurately reflect the exact shade or batch supplied, as variation is an inherent property of tiles and stone. Listed sizes and thicknesses are nominal and may vary slightly from actual working dimensions.



available sizes



150x150mm



60x240mm



300x300mm



pictured: light

Sutherland Sharks Football Club
 designed: Five Foot One Design
 photography: Ryan Linnegar



pictured: dark

Fortune Alley Macquarie
designed: Span Design





technical data - tiles

properties	test method	value
WATER ABSORPTION	ISO 10545-3	7.09%
BENDING STRENGTH	ISO 10545-4	20.7 MPa
IMPACT RESISTANCE	ISO 10545-5	0.80
ABRASION RESISTANCE	ISO 10545-6	215 mm ³
RESISTANCE TO FROST	ISO 10545-12	>100
MOISTURE EXPANSION	ISO 10545-10	0.228 mm/m
SURFACE SCRATCH HARDNESS	-	0.67 dry 0.58 wet

Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.

- Sealing is required prior and post grouting for all sizes.
- Dark grout colours are not recommended.
- Minimum 10mm grout joints are recommended

