



skheme®

yugen split



white



clay



grey

yugen split



mosaic

180x330mm



3D format



mosaic



wall only



external wall safe



V2

PRODUCT SPECIFICATIONS	format	size	finish	thickness	slip rating	colour
	mosaic	180x330mm	mat	random	N/A	all colours
MATERIAL	unglazed porcelain					
VARIATION	V2					
TILE EDGE	rectified					

Colours shown in images may differ due to variations in photographic conditions and screen displays. Samples provided may not accurately reflect the exact shade or batch supplied, as variation is an inherent property of tiles and stone. Listed sizes and thicknesses are nominal and may vary slightly from actual working dimensions.



left pictured: white, clay & grey
right pictured: white



technical data

properties	test method	prescribed values	value
WATER ABSORPTION	ISO 10545-3	0.5%<Eb ≤3%	1.4%
MODULUS OF RUPTURE	ISO 10545-4	Minimum 30	44.1
BREAKING STRENGTH	ISO 10545-4	≥1100	6937
SURFACE QUALITY	ISO 10545-2	95% free of visible defects	100%
RESISTANCE TO CHEMICALS	ISO 10545-13	Minimum class B	A
RESISTANCE TO STAINING	ISO 10545-14	Declared value	Class 5

Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.



The information provided in this Technical Data Sheet is given in good faith and reflects current knowledge and experience. It is intended as a general guide and may be updated without notice. Users are responsible for ensuring the product's suitability for their specific application and for compliance with all relevant local building codes, Australian Standards, and regulations. This information is offered for guidance purposes only and does not constitute any representation or warranty, express or implied. Any applicable warranties are governed solely by the terms and conditions of sale and relevant statutory requirements under Australian Consumer Law.