

AVENUE is a hybrid of stone and limestone look tiles. With subtle movement and colour variation which can be applied for internal wall and floors.

**PRODUCT TYPE**: Glazed Porcelain

**COLOURS:** White, Mist, Fawn and Stone

**SIZES:** 300x300mm, 300x600m and 600x600mm

Rectified Edges

FINISHES/USAGE: Matt, and Grip/Wall and Floor

**AESTHETIC QUALITIES:** Limestone look

TECHNICAL INFO: Matt - P2 Pendulum Slip rating

Grip - P5 Pendulum Slip rating More information on last page

VARIATION:







### PRODUCT SPECIFICATIONS

FINISHES	TILE EDGE	SLIP RATING
MAH	RECTIFIED	P2 Pendulum
MATT	RECTIFIED	P2 Pendulum
MATT	RECTIFIED	P2 Pendulum
GRIP	RECTIFIED	P5 Pendulum
	MATT MATT MATT	MATT RECTIFIED MATT RECTIFIED MATT RECTIFIED

### **FORMATS**



#### **WHITE**



MATT

### **FAWN**






Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.



### PRODUCT SPECIFICATIONS

SIZES	FINISHES	TILE EDGE	SLIP RATING
300x300mm	MATT	RECTIFIED	P2 Pendulum
300X600mm	MATT	RECTIFIED	P2 Pendulum
600x600mm	MATT	RECTIFIED	P2 Pendulum
300x600mm	GRIP	RECTIFIED	P5 Pendulum

### **FORMATS**



#### **MIST**



### **STONE**



Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.







#### TECHNICAL DATA

technical characteristics	test method	required values	value
 water absorption	iso 10545-3	0,5% < E ≤ 3%	-
 breaking strength (S)	iso 10545-4	≥ 1300 N	pass
thermal shock resistance	iso 10545-9	no visible defects	pass
chemical resistance	iso 10545-13	Class A	pass
length and width of the average sizes	iso 10545-2	± 0,5%	pass
thickness	iso 10545-2	± 0,5%	pass
straightness of sides	iso 10545-2	± 0,5% and ±1.5mm	pass
surface quality	iso 10545-2	minimum of 95% of tiles free from visible defects	pass