skheme®



travstone cross



travstone cross

Add a refreshed lightness to the room with our Travstone Cross porcelain range. Simple, inviting and cohesive, these tiles embody an inherent natural quality to suit a wide range of indoor-outdoor applications. Featuring three beautiful colours with gentle organic crosscut veining.



DIMENSIONS		150x 150mm	matt	all colours
		300x600mm	matt	all colours
		600x600mm	matt	all colours
		600x1200mm	matt	all colours
	3D combed	600x 1200mm	combed	all colours
	paver	600x600x20mm	grip	all colours
	paver coping	400x600x20mm	grip	all colours

	slab	1200x2700x6mm	matt	pearl
MATERIAL				glazed porcelain
VARIATION				V2
TILE EDGE				rectified
THICKNESS			tile slab paver	10mm 6mm 20mm
SLIP RATING		matt grip paver	P4 P5 P5	indoor & outdoor indoor & outdoor indoor & outdoor



cream

argent



pearl



TRAVSTONE CROSS PAVER

400x600x20mm 600x600x20mm



pearl





TRAVSTONE CROSS 3D COMBED

600x1200mm





left pictured: pearl right pictured: argent

technical data

PROPERTIES	TEST METHOD	PRESCRIBED VALUES	VALUE
water absorption	ISO 10545-3	≤0.5%	≤0.4%
bending strength	ISO 10545-4	≥35 N/ mm2	compliant
thermal shock resistance	ISO 10545-9	No sample must show visible defects	compliant
deep abrasion resistance	ISO 10545-6	≤ 175 mm3	compliant
resistance to chemicals	ISO 10545-13	Declared value	compliant
resistance to frost	ISO 10545-12	Resistant	compliant
resistance to staining	ISO 10545-14	Minimum class 3	compliant
surface quality	ISO 10545-2	Complies with the standards	≥95%



Please note that all products must be fabricated using score & snap method and/or wet cutting in conjunction with AS/NZS 1716:2012, AS/NZS 1715:2009, AS/NZS 60335.2.69:2017. For more information please refer to: https://www.safework.nsw.gov.au

Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.