

skheme®

claire stone





# claire stone




cotton




almond



mink



300x300mm



600x600mm



300x600mm



600x1200mm



fire resistant



sustainable



cost effective



outdoor



P3 slip rating



P4 slip rating



V2 variation

PRODUCT SPECIFICATIONS			format	size	finish	thickness	slip rating	colour
	tile	300x300mm	matt   grip	matt	10mm	P3	P3	all colours
	tile	300x600mm		matt	10mm	P3   P4	P4	all colours
	tile	600x600mm		matt	10mm	P3	P3	all colours
	tile	600x1200mm		matt	10mm	P3	P3	all colours
MATERIAL							glazed porcelain	
VARIATION								V2
TILE EDGE								rectified

Colours shown in images may differ due to variations in photographic conditions and screen displays. Samples provided may not accurately reflect the exact shade or batch supplied, as variation is an inherent property of tiles and stone.

Listed sizes are nominal and may vary slightly from actual working dimensions.

A 2/12-14 Neild Avenue Rushcutters Bay NSW 2010 | P 02 8755 2300 | W [www.skheme.com](http://www.skheme.com) | E [info@skheme.com](mailto:info@skheme.com)

left pictured: cotton  
right pictured: cotton



johnson winter slattery by bates smart & renascent

## technical data

PROPERTIES	TEST METHOD	PRESCRIBED VALUES	VALUE
water absorption	ISO 10545-3	≤0.5%	≤0.4%
bending strength	ISO 10545-4	≥ 12 MPA	≥ 33.5MPA
breaking strength	ISO 10545-4	≥ 350 N	780N
abrasion resistance	ISO 10545-7	Max. 175 mm <sup>3</sup> PEI 1-5	class 3
resistance to chemicals	ISO 10545-13	Household chemicals & swimming pool salts	GA
		Low concentration of acids & alkalis	GLA
resistance to staining	ISO 10545-14	Minimum class 3	class 5



ISO 14001:2015 specifies the requirements for an environmental management system that an organization can use to enhance its environmental performance. ISO 14001:2015 is intended for use by an organization seeking to manage its environmental responsibilities in a systematic manner that contributes to the environmental pillar of sustainability.

Please note that all products must be fabricated using score & snap method and/or wet cutting in conjunction with AS/NZS 1716:2012, AS/NZS 1715:2009, AS/NZS 60335.2.69:2017. For more information please refer to: <https://www.safework.nsw.gov.au>

Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.

A 2/12-14 Neild Avenue Rushcutters Bay NSW 2010 | P 02 8755 2300 | W [www.skheme.com](http://www.skheme.com) | E [info@skheme.com](mailto:info@skheme.com)