

skheme®



elara

elara



white


tawn



300x300mm



300x600mm



600x600mm



600x1200mm



fire
resistant



cost
effective



P3
slip
rating



P5
slip
rating



variation V3

PRODUCT SPECIFICATIONS

format	size	finish	thickness	slip rating	colour
tile	300x300mm	matt	10mm	P3	all colours
tile	300x600mm	matt grip	10mm	P3 P5	all colours
tile	600x600mm	matt	10mm	P3	all colours
tile	600x1200mm	matt	10mm	P3	all colours

MATERIAL

glazed porcelain

VARIATION

V3

TILE EDGE

rectified

Colours shown in images may differ due to variations in photographic conditions and screen displays. Samples provided may not accurately reflect the exact shade or batch supplied, as variation is an inherent property of tiles and stone.

Listed sizes and thicknesses are nominal and may vary slightly from actual working dimensions.

A 2/12-14 Neild Avenue Rushcutters Bay NSW 2010 | P 02 8755 2300 | W www.skheme.com | E info@skheme.com

left pictured: tawn
right pictured: tawn



technical data

properties	test method	prescribed value	value
WATER ABSORPTION	ISO 10545-3	≤0.5%	0.5%
BENDING STRENGTH	ISO 10545-4	≥ 12 MPA	≥ 33.5MPA
BREAKING STRENGTH	ISO 10545-4	≥ 350N	1785 N
ABRASION RESISTANCE	ISO 10545-7	Max. 175 mm ³ PEI 1-5	Class 3
RESISTANCE TO CHEMICALS	ISO 10545-13	Household chemicals & swimming pool salts Low concentration of acids & alkalis	Pass
CRAZING RESISTANCE	ISO 10545-11	No cracking or peeling	Pass



ISO 14001:2015 specifies the requirements for an environmental management system that an organization can use to enhance its environmental performance. It is intended for use by an organization seeking to manage its environmental responsibilities in a systematic manner that contributes to the environmental pillar of sustainability.



AN ENVIRONMENTAL PRODUCT DECLARATION (EPD) is a globally recognised certification that outlines the environmental impact of a product across its entire life cycle. It supports sustainable decision-making and green procurement by assessing factors such as material sourcing, emissions, installation, use, and end-of-life disposal.



Please note that all products must be fabricated using score & snap method and/or wet cutting in conjunction with AS/NZS 1716:2012, AS/NZS 1715:2009, AS/NZS 60335.2.69:2017. For more information please refer to: <https://www.safework.nsw.gov.au>