Jazz



A collection of 100x300mm Porcelain Glazed tiles with gloss and matt finishes, suitable for floor and external facades. JAZZ comes in a broad palette, consisting of vibrant colours with combinations of shades and chromatic effects. The glazed gloss and matt tiles can also be provided with an Antibacterial Protection* enriching the tiles with more hygiene and ease of maintenance.

The modular structure of JAZZ and TECNICA lets designs of different magnitudes occur in coherence. Different sizes of floor and wall tiles are produced in accordance with 3 mm joint spaces. Combine both these series for limitlessly usages of interior spaces.

PRODUCT TYPE:	Porcelain Glazed matt and gloss tile	
COLOURS:	White, Pale Grey, Charcoal, Black, Yellow, Red and Cobalt	
SIZES:	100x300mm Non-rectified edges	
FINISHES/USAGE:	Matt/Floor (soft shoe only) Gloss/Wall only	
STHETIC QUALITIES:	A modular sleek tile in an abundance of colours that are complementary to each other	
TECHINICAL INFO:	*A 200 metre minimum order is required when ordering Antibacterial protection	
	More technical data on the last page.	
ORIGIN:	Turkey	
VARIATION:		



Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint. Visit<u>http://www.skheme.com/Conditions.aspx</u> for all disclaimer, copyright and terms and conditions.

Jazz

PRODUCT SPECIFICATIONS SIZES FINISHES TILE EDGE 100x300mm GLOSS NON-RECTIFIED 100x300mm MATT NON-RECTIFIED WHITE GLOSS FORMATS WHITE MATT 100x300mm **BLACK GLOSS**

Jazz

PRODUCT SPECIFICATIONS

SIZES	FINISHES	TILE EDGE
100x300mm 100x300mm		NON-RECTIFIED NON-RECTIFIED

FORMATS

100x300mm



CHARCOAL GLOSS



CHARCOAL MATT



Jazz

PRODUCT SPECIFICATIONS

SIZES	FINISHES	TILE EDGE
100x300mm	GLOSS	NON-RECTIFIED





FORMATS

100x300mm	

RED GLOSS



COBALT GLOSS



Jazz

MATT AND GLOSS

	technical characteristics	test method	required values	value
۵ ۵ ۵ ۵ ۵	water absorption	iso 10545-3	0,5% <e≤ 3%<="" th=""><th>0,5%<e≤ 3%<="" th=""></e≤></th></e≤>	0,5% <e≤ 3%<="" th=""></e≤>
	frost resistance	iso 10545-12	no alterations	resistant
Ĝĉ	breaking strength (S)	iso 10545-4	Min. 1300N For thickness≥7,5mm Min. 700N For thickness<7,5mm	>700N
<u>+</u>	thermal shock resistance	iso 10545-9	test method available	resistant
	chemical resistance	iso 10545-13	resistant	resistant
2	stain resistance	iso 10545-14	test method available	class 3
()	surface abrasion	iso 10545-7	Report Abrasion Class and cycles passed	PEI 1-4





ISO:14001 2004

ANTIBACTERIAL TREATMENT*

The wall tile can be treated with an antibacterial treatment that is added before the firing process and has a life expectancy equal to the tile itself. Antibacterial treatment is added protection for spaces where superior health and hygiene are a must such as hospitality and medical areas.

*A 200 metre minimum order is required when ordering this extra feature.