



ARIA is a contemporary series that displays subtle movement and colour variation for a soft limestone look. Available in four colours and three finishes including a feature chevron tile. ARIA is able to add extra design elements to any environment.

PRODUCT TYPE: Porcelain Glazed Tile

COLOURS: Ivory, Ash, Taupe and Deep Taupe

SIZES: 300x300mm 300x600mm and

600x600mm Rectified edges

FINISHES/USAGE: Matt/Wall and Floor

Grip/Floor Only Chevron/ Wall Only

AESTHETIC QUALITIES: Subtle movement and colour variation

TECHINICAL INFO: P3 Pendulum Slip rating/Matt

P4 Pendulum Slip rating/Grip

There is inherent variation in colour and calibration between Aria base tiles and Aria Chevron tiles due to the different

production process.

Please inspect the tiles carefully prior to

installation.

More technical data on last page

VARIATION:





PRODUCT SPECIFICATIONS

SIZES	FINISHES	SLIP RATING	TILE EDGE
300x300mm	MATT	P3 Pendulum	RECTIFIED
300x600mm	MATT	P3 Pendulum	RECTIFIED
600x600mm	MATT	P3 Pendulum	RECTIFIED
300x600mm*	GRIP	P4 Pendulum	RECTIFIED
300x600mm	CHEVRON	-	RECTIFIED

^{*}Please note - Ivory is not available in the Grip finish






IVORY

ASH

IVORY CHEVRON



600x600mm





ASH CHEVRON



PRODUCT SPECIFICATIONS

FINISHES	SLIP RATING	TILE EDGE
MATT	P3 Pendulum	RECTIFIED
MATT	P3 Pendulum	RECTIFIED
MATT	P3 Pendulum	RECTIFIED
GRIP	P4 Pendulum	RECTIFIED
CHEVRON	-	RECTIFIED
	MATT MATT MATT GRIP	MATT P3 Pendulum MATT P3 Pendulum MATT P3 Pendulum GRIP P4 Pendulum


^{*}Please note - Ivory is not available in the Grip finish





TAUPE

TAUPE CHEVRON



600x600mm





DEEP TAUPE

DEEP TAUPE CHEVRON



TECHNICAL DATA

Tec	hnical Characteristi s	Test Method	Requirement	Result
Suri	face quality	ISO 10545-2	95%	100%
Len	gth and Width	ISO 10545-2	‡ 0,6%	0.5%
Thio	ckness	ISO 10545-2	‡ 0,5	‡ 0,5
Stra	ightness of sides	ISO 10545-2	‡ 0,5%	‡ 0,3%
Wat	er Absorbtion	ISO 10545-3	3%	3%
Mod	dulus of Rupture	ISO 10545-4	35	38
Brea	aking Strength	ISO 10545-4	1100	1300
Cra	zing Resistance	ISO 10545-11	Pass	Resistant
Che	mical Resistance	ISO 10545-13	Declared Value	ULA / UHB
Stai	n Resistance	ISO 10545-14	Minimum Class 3	Class 5











