

Avenue



PRODUCT TYPE: Glazed, colour bodied porcelain

COLOURS: White, Mist, Fawn and Stone


SIZES: 300x300mm, 300x600mm, 600x600mm and
200x200mm, 450x900mm*
Rectified Edges

FINISHES/USAGE: Matt, Grip & Matt /Wall and Floor

AESTHETIC QUALITIES: Limestone look

TECHNICAL INFO: Matt - P2 'Y' Pendulum Slip rating
Grip - P5 'V' Pendulum Slip rating

VARIATION:



V2

AVENUE is a hybrid of stone and limestone look tiles. With subtle movement and colour variation, each of the four colours is available in matt and grip finish which can be applied for internal wall & floors.



Avenue

PRODUCT SPECIFICATIONS

SIZES	FINISHES	TILE EDGE	SLIP RATING
300x300mm	MATT	RECTIFIED	P2 'Y' Pendulum
300x600mm	MATT	RECTIFIED	P2 'Y' Pendulum
600x600mm	MATT	RECTIFIED	P2 'Y' Pendulum
300x600mm	GRIP	RECTIFIED	P5 'V' Pendulum
450x900mm*	MATT	RECTIFIED	P2 'Y' Pendulum

* Indent item - Subject to stock availability overseas, please allow 6-10 weeks lead time from date of order confirmation. Minimum quantity may apply.

FORMATS



WHITE



MATT



GRIP

FAWN



MATT



GRIP



Avenue

PRODUCT SPECIFICATIONS

SIZES	FINISHES	TILE EDGE	SLIP RATING
300x300mm	MATT	RECTIFIED	P2 'Y' Pendulum
300x600mm	MATT	RECTIFIED	P2 'Y' Pendulum
600x600mm	MATT	RECTIFIED	P2 'Y' Pendulum
300x600mm	GRIP	RECTIFIED	P5 'V' Pendulum
450x900mm*	MATT	RECTIFIED	P2 'Y' Pendulum

* Indent item - Subject to stock availability overseas, please allow 6-10 weeks lead time from date of order confirmation. Minimum quantity may apply.

FORMATS



MIST



MATT



GRIP

STONE



MATT



GRIP

Avenue

technical characteristics	test method	required values	value
water absorption	iso 10545-3	0,5% < E ≤ 3%	-
breaking strength (S)	iso 10545-4	≥ 1300 N	pass
thermal shock resistance	iso 10545-9	no visible defects	pass
chemical resistance	iso 10545-13	Class A	pass
length and width of the average sizes	iso 10545-2	± 0,5%	pass
thickness	iso 10545-2	± 0,5%	pass
straightness of sides	iso 10545-2	± 0,5% and ±1.5mm	pass
surface quality	iso 10545-2	minimum of 95% of tiles free from visible defects	pass