



TRELLIS consists of two contemporary textures - wood and concrete, moulded and imprinted onto a single, large sized stoneware slab. The colour range is neutral, suitable for any location. The distinctive combination of surfaces creates a versatile collection suitable for indoor and outdoor use in both residential and commercial settings.

PRODUCT TYPE: Glazed Porcelain

COLOURS: White, Ice, Smoke, Clay and Wood

SIZES: 600x600mm and 200x200mm

Rectified Edges

FINISHES/USAGE: Blend Textured. Textured, Birch Textured

and Solid Matt Wall and Floor

AESTHETIC QUALITIES: Wood and concrete look

TECHNICAL DATA: More technical data on the last page

P3 Pendulum Slip rating (All colours

except Trellis White)

VARIATION:





PRODUCT SPECIFICATIONS

| SIZES | FINISHES | TILE EDGE | SLIP RATING |
|-----------|----------------|-----------|---------------|
| 200x200mm | BLEND TEXTURED | RECTIFIED | P3 Pendulum** |
| 600x600mm | BLEND TEXTURED | RECTIFIED | P3 Pendulum** |
| 600x600mm | SOLID MATT | RECTIFIED | P3 Pendulum** |


- * Indent item Subject to stock availability overseas, please allow 10-12 weeks lead time from date of order confirmation. Minimum quantity may apply.
- $^{*}\,^{*}$ Trellis White Blend Textured and Trellis White Solid Matt are not rated P3 Pendulum

FORMATS

200x 200mm

600x600mm





WHITE SOLID MATT



ICE BLEND TEXTURED



ICE SOLID MATT*



SMOKE BLEND TEXTURED



SMOKE SOLID MATT*



PRODUCT SPECIFICATIONS

| SIZES | FINISHES | TILE EDGE | SLIP RATING |
|-----------|----------------|-----------|-------------|
| 200x200mm | BLEND TEXTURED | RECTIFIED | P3 Pendulum |
| 600x600mm | BLEND TEXTURED | RECTIFIED | P3 Pendulum |
| 600x600mm | SOLID MATT | RECTIFIED | P3 Pendulum |
| 600x600mm | TEXTURED | RECTIFIED | P3 Pendulum |
| 600x600mm | BIRCH TEXTURED | RECTIFIED | P3 Pendulum |

^{*} Indent item - Subject to stock availability overseas, please allow 10-12 weeks lead time from date of order confirmation. Minimum quantity may apply.

FORMATS

200x 200mm

600x600mm



CLAY BLEND TEXTURED*



CLAY SOLID MATT*



WOOD TEXTURED*



WOOD BIRCH TEXTURED*











TECHNICAL DATA

| | technical characteristics | test method | value |
|--------------|----------------------------|--------------|-----------------------------------|
| δ δ δ δ δ | water absorption | iso 10545-3 | E <=0,04% |
| | frost resistance | iso 10545-12 | complies with standard |
| Ĝ Ĉ | bending strength | iso 10545-4 | 53 N/mm² |
| Ö | resistace to deep abrasion | iso 10545-6 | <128mm³ complies with standard |
| <u>+</u> | thermal shock resistance | iso 10545-9 | complies with standard |
| R | chemical resistance | iso 10545-13 | UA ULA UHA |
| <i>←</i> | slip resistance | din 51130 | R10 |