Woodlot



WOODLOT is produced using hi-definition inkjet technology with a slightly textured finish and
wood graining to recreate a natural timber look tile. Also available in a chevron tile allowing
for creative pattern-making.

PRODUCT TYPE:	Glazed Porcelain		
COLOURS:	White Oak, Acacia and Walnut		
SIZES:	200x1200mm and 100x600mm Chevron		
FINISHES/USAGE:	Rectified edges		
AESTHETIC QUALITIES:	Matt/Wall & floor		
	The digital system gurantees realistic, authentic colouring, with variations in texture and patterning.		
TECHNICAL INFO:	Matt - P3 Pendulum Slip rating		
VARIATION:	V3		

Woodlot

PRODUCT SPECIFICATIONS

SIZES	FINISHES	TILE EDGE	SLIP RATING
200x1200mm	MATT	RECTIFIED	P3 Pendulum
100x600mm	MATT CHEVRON	RECTIFIED	P3 Pendulum

Brick bond laying pattern where the grout joint is in the middle of the adjacent tile is not suggested as it highlights potential flatness irregularities. Due to surface flatness tolerance in most large size tiles (including timber look tiles), it is suggested to offset the tiles with no more than 30% of the tile length. Eg. 1200mm long, should be laid with an offset no larger than 300mm.



WHITE OAK MATT



ACACIA MATT



FORMATS

200x1200mm

100x600mm

WALNUT MATT

Woodlot

PRODUCT SPECIFICATIONS

SIZES	FINISHES	TILE EDGE	SLIP RATING
200x1200mm	MATT	RECTIFIED	P3 Pendulum
100x600mm	MATT CHEVRON	RECTIFIED	P3 Pendulum

Brick bond laying pattern where the grout joint is in the middle of the adjacent tile is not suggested as it highlights potential flatness irregularities. Due to surface flatness tolerance in most large size tiles (including timber look tiles), it is suggested to offset the tiles with no more than 30% of the tile length. Eg. 1200mm long, should be laid with an offset no larger than 300mm.

FORMATS

200x1200mm		
100x600mm		





Woodlot



Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.



Woodlot



Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.

Woodlot

TECHNICAL DATA

	technical characteristics	test method	value	
8 8 8 8 8	water absorption	iso 10545-3	<0,5%	
業	frost resistance	iso 10545-12	it stands the test	
± i	thermal shock resistance	iso 10545-9	it stands the test	
R	chemical resistance to cleaning products	iso 10545-13	GA	
2	stain resistance	iso 10545-14	5	